



**ARCHITECT NOTE:**

- DETAIL FOR UNSUPPORTED PROGUARD DP® - DOUBLE DRAINAGE PLANE PANELS.
- ENGINEER OF RECORD TO SELECT PROGUARD DP® SCREW SPACING USING NTA REPORT TRIG030116-28.

INSULATION CHAMFERED AT TOP AND BOTTOM OF PANEL EDGES TO ALLOW FOR CONTINUOUS DRAINAGE  
 1'-0" x 8'-0" PROGUARD DP® BASE WEEP PANEL - DOUBLE DRAINAGE PLANE AT ALL FLASHING LOCATIONS  
 STEEL TRACK FASTENER (SCREW SIZE IS DETERMINED BY LOAD SUPPORTED)  
 STEEL TRACK  
 FLASHING MEMBRANE ADHERED MIN. 4" UP SUBSTRATE. OVERLAP AIR / WATER BARRIER OVER FLASHING

THIN-CLAD CALCIUM SILICATE TILE,  
 MVIS™ HI-BOND VENEER MORTAR -  
 POLYMER FORTIFIED,  
 PROGUARD DP® INSULATED CONCRETE  
 BOARD PANEL - DOUBLE DRAINAGE  
 PLANE (THICKNESS DEPENDENT ON  
 REQUIRED R-VALUE),  
 MVIS™ AIR & WATER BARRIER or  
 WATERARMOR® AWB,  
 EXTERIOR SHEATHING,  
 STEEL STUD WALL,  
 VAPOR BARRIER (LOCATION  
 DEPENDENT ON CLIMATE ZONE),  
 GYPSUM WALLBOARD

ATTACH PROGUARD DP® PANELS  
 WITH SILVER C APPROVED SCREWS  
 THROUGH TO STUDS (TYPICAL)

TAPE JOINT WITH ALKALI-RESISTANT  
 MESH TAPE AND MUD JOINT WITH  
 MVIS™ HI-BOND VENEER MORTAR

MVIS™ POINTING MORTAR

COMPRESSIBLE BACKER ROD  
 AND SILICONE SEALANT w/  
 WEEP HOLES @ 8" o.c.

PREFINISHED METAL DRIP EDGE

COMPRESSIBLE  
 BACKER ROD AND  
 SILICONE SEALANT

PREMOLDED EXPANSION  
 JOINT FILLER

PARGING



**ARRISCRAFT-CADD**

DETAIL No:  
 SS08SAT - DP2U

TITLE:  
 ALTERNATIVE FOUNDATION TO  
 WALL JUNCTION WITH PAVING

**U009**

DATE DRAWN: 16 Jan 2021  
 SCALE: 3"=1'-0"  
 DRAWN BY: TRI