

CALCIUM SILICATE MASONRY UNIT (CSMU),  
 MIN. 1" AIR SPACE,  
 RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE),  
 AIR/VAPOR BARRIER MEMBRANE,  
 EXTERIOR SHEATHING,  
 STEEL STUD WALL,  
 GYPSUM WALLBOARD.

SEALANT BEADS FOR MOISTURE PROTECTION

SLOPED SILL AWAY TO ENSURE WATER DRAINAGE

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

COMPRESSIBLE BACKER ROD AND SEALANT

HIGH SLUMP MASONRY GROUT

ADAIR® LIMESTONE MARBLE BASE COURSE

COMPRESSIBLE BACKER ROD AND SEALANT

PREMOLDED EXPANSION JOINT FILLER

2% SLOPE MIN.

PREMANUFACTURED THERMALLY BROKEN ALUMINUM DOOR ASSEMBLY

COMPRESSIBLE BACKER ROD AND SEALANT

FLOOR BY OTHER

BUILDING PAPER

AIR/VAPOR BARRIER



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

THRESHOLD OF DOOR  
 WITH ADAIR® BASE COURSE

DATE DRAWN:  
 08/30/04

SCALE:  
 3"=1'-0"

DRAWN BY:  
 LPS

DETAIL No:  
 SS 08S

**U051**