



INSULATION
RETAINER
ADJUSTABLE
WALL TIE

GYPSUM WALLBOARD
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER MEMBRANE,
RIGID OR SEMI-RIGID INSULATION
(THICKNESS DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
CALCIUM SILICATE MASONRY
UNIT (CSMU).

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

STEEL TRACK FASTENER
(SCREW SIZE IS
DETERMINED BY
LOAD SUPPORTED)

MORTAR DROP
CONTROL

STEEL TRACK

WELD PLATE
CAST IN PLACE

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

PREFINISHED
METAL DRIP EDGE
SET ON TWO BEADS
OF SEALANT

3/8" MIN.

COMPRESSIBLE
BACKER ROD
AND SEALANT

LONG LEG OUTER
TRACK ANCHORED TO
SLAB, NEITHER SHEATHING
OR DRYWALL ATTACHED
TO ALLOW FOR
DEFLECTION OF SLAB

CORROSION PROTECTED
CONTINUOUS STEEL
ANGLE AND STEEL BRACKET

MINERAL FIBER
FIRE STOP WHERE
REQUIRED

VENT @ 24" O/C



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE: **SHELF ANGLE/WALL**

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
SS 08S

U080