



GYPSUM WALLBOARD,
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER MEMBRANE,
 16 GAUGE Z-CHANNEL,
 RIGID OR SEMI RIGID INSULATION
 (THICKNESS DEPENDANT ON
 REQUIRED R-VALUE),
 ALUMINUM CHANNELS,
 1" AIR SPACE,
 CALCIUM SILICATE CLIP UNIT

BACKER ROD AND
 SEALANT

REQUIRED SHIM TO
 SEPARATE
 ALUMINUM CHANNEL
 FROM Z-CHANNEL, MAX.
 SHIMS 3/4" THICK

FLASHING MEMBRANE
 ADHERED TO SUBSTRATE

SILICONE COMPATIBLE
 WEEP VENT @ 24" O/C

PREFINISHED
 METAL DRIP EDGE

Z-CHANNEL FASTENERS @ 16" O.C.
 C/W SHIMS AS REQUIRED, MAX.
 SHIMS 3/4" THICK

COMPRESSIBLE BACKER
 ROD AND SEALANT

STEEL TRACK FASTENER
 (SCREW SIZE IS
 DETERMINED BY
 LOAD SUPPORTED)

STEEL TRACK
 SILL FLASHING

PARGING
 6" MIN.

2% SLOPE MIN



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 FOUNDATION TO WALL
 JUNCTION WITH SOIL

DATE DRAWN:
 01/15/12

SCALE:
 3"=1'-0"

DRAWN BY:
 D.D.N.

DETAIL No:
 SS 12RU

AC000