



- GYPSUM WALLBOARD,
- STEEL STUD WALL,
- STEEL STUD FURRING,
- EXTERIOR SHEATHING,
- AIR/VAPOR BARRIER MEMBRANE,
- 16 GAUGE Z-CHANNEL,
- RIGID OR SEMI RIGID INSULATION
(THICKNESS DEPENDANT ON
REQUIRED R-VALUE),
- ALUMINUM CHANNELS,
- 1" AIR SPACE,
- CALCIUM SILICATE CLIP UNIT
- REQUIRED SHIM TO SEPARATE
ALUMINUM CHANNEL FROM
Z-CHANNEL, MAX. SHIMS 3/4" THICK
- Z-CHANNEL FASTENERS
@ 16" O.C. C/W SHIMS AS
REQUIRED, MAX. SHIMS
3/4" THICK
- FLASHING MEMBRANE
ADHERED TO SUBSTRATE
- SHEET METAL ANGLE ATTACHED
TO SOFFIT "Z" CHANNELS (ALL
SAME GAUGE)
- 1 3/4"
- 1 3/4"
- COMPRESSIBLE BACKER
ROD AND SEALANT
- UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C
- WOOD BLOCKING
- SPRAY APPLIED FOAM INSULATING
AIR SEAL ALL AROUND FRAME
- PREMANUFACTURED
THERMALLY BROKEN ALUMINUM
WINDOW ASSEMBLY



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

OPTIONAL RECESSED
ALUMINUM WINDOW HEAD

DATE DRAWN:
01/15/12

SCALE:
3"=1'-0"

DRAWN BY:
D.D.N.

DETAIL No:

SS 12RU

AC033