



BACKER ROD AND SEALANT

SLOPED WATERTABLE
CALCIUM SILICATE
CLIP UNIT

DRIP CUT

FLASHING MEMBRANE
ADHERED TO SUBSTRATE

REQUIRED SHIM TO
SEPARATE
ALUMINUM CHANNEL
FROM Z-CHANNEL, MAX.
SHIMS 3/4" THICK

BACKER ROD AND
SEALANT

Z-CHANNEL FASTENERS
@ 16" O.C. C/W SHIMS AS
REQUIRED, MAX. SHIMS
3/4" THICK

GYPSUM WALLBOARD,
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER MEMBRANE,
16 GAUGE Z-CHANNEL,
RIGID OR SEMI RIGID INSULATION
(THICKNESS DEPENDANT ON
REQUIRED R-VALUE),
ALUMINUM CHANNELS,
1" AIR SPACE,
CALCIUM SILICATE CLIP UNIT



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

SLOPED WATERTABLE

DATE DRAWN:
01/15/12

SCALE:
3"=1'-0"

DRAWN BY:
D.D.N.

DETAIL No:
SS 12RU

AC101