



GYPSUM WALLBOARD  
 STEEL STUD WALL,  
 EXTERIOR SHEATHING,  
 AIR/VAPOR BARRIER  
 MEMBRANE,  
 RIGID OR SEMI-RIGID INSULATION  
 (THICKNESS DEPENDANT ON  
 REQUIRED R-VALUE),  
 MIN. 1" AIR SPACE,  
 CALCIUM SILICATE  
 MASONRY UNIT (CSMU).

STEEL TRACK FASTENER  
 (SCREW SIZE IS  
 DETERMINED BY  
 LOAD SUPPORTED)  
 STEEL TRACK

ADJUSTABLE WALL TIE  
 INSULATION RETAINER  
 FLASHING MEMBRANE  
 SURFACE ADHERE  
 TO SUBSTRATE  
 MORTAR DROP  
 CONTROL  
 UNOBSTRUCTED  
 WEEP SYSTEM @ 24" O/C

PREFINISHED  
 METAL DRIP EDGE  
 SET ON TWO BEADS  
 OF SEALANT

3/8" MIN. PARGING  
 6" MIN.  
 COMPRESSIBLE BACKER  
 ROD AND SEALANT  
 PREMOULDED EXPANSION  
 JOINT FILLER

2% SLOPE MIN.

WELD PLATE  
 CAST IN PLACE  
 BUILDING PAPER  
 STEEL STUD  
 FURRING WITH  
 INSULATION  
 AIR/VAPOR  
 BARRIER



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
 ALTERNATIVE FOUNDATION TO WALL  
 (SHELF ANGLE) WITH PAVING

DATE DRAWN:  
 08/30/04

SCALE:  
 3"=1'-0"

DRAWN BY:  
 LPS

DETAIL No:  
 SS 12R

**U008**