



GYPSUM WALLBOARD
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER MEMBRANE,
 RIGID OR SEMI-RIGID INSULATION
 (THICKNESS DEPENDANT ON
 REQUIRED R-VALUE),
 MIN. 1" AIR SPACE,
 CALCIUM SILICATE MASONRY
 UNIT (CSMU).

STEEL TRACK FASTENER
 (SCREW SIZE IS
 DETERMINED BY
 LOAD SUPPORTED)

STEEL TRACK
 WELD PLATE
 CAST IN PLACE

LONG LEG OUTER
 TRACK ANCHORED TO
 SLAB, NEITHER SHEATHING
 OR DRYWALL ATTACHED
 TO ALLOW FOR
 DEFLECTION OF SLAB

MINERAL FIBER
 FIRE STOP WHERE
 REQUIRED

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

MORTAR DROP
 CONTROL

UNOBSTRUCTED
 WEEP SYSTEM @ 24" O/C

PREFINISHED
 METAL DRIP EDGE
 SET ON TWO BEADS
 OF SEALANT

3/8" MIN.

COMPRESSIBLE
 BACKER ROD
 AND SEALANT

CORROSION PROTECTED
 CONTINUOUS STEEL
 ANGLE AND STEEL BRACKET

VENT @ 24" O/C

INSULATION
 RETAINER
 ADJUSTABLE
 WALL TIE



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 SHELF ANGLE/WALL

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 SS 12R

U080