



SEALANT BEADS FOR
MOISTURE PROTECTION

SLOPE SILL AWAY TO
ENSURE WATER DRAINAGE

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM DOOR
ASSEMBLY

CAST IN PLACE
CONCRETE CURB

CAST IN PLACE
CONCRETE CURB

VERTICAL REINFORCING
IF REQUIRED

BALCONY SUPPORTED BY
POSTS AT EXTERIOR EDGES

COMPRESSIBLE BACKER
ROD AND SEALANT

VENT @ 24" O/C

CORROSION PROTECTED
CONTINUOUS STEEL
ANGLE AND STEEL BRACKET

WELD PLATE
CAST IN PLACE

LONG LEG OUTER
TRACK ANCHORED TO
SLAB, NEITHER SHEATHING
OR DRYWALL ATTACHED
TO ALLOW FOR
DEFLECTION OF SLAB



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

BALCONY/WALL
AT PATIO DOOR

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:

SS 12R

U092