

CALCIUM SILICATE MASONRY
UNIT (CSMU),
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON REQUIRED
R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
EXTERIOR SHEATHING,
STEEL STUD WALL,
GYPSUM WALLBOARD.

SEALANT BEADS FOR
MOISTURE PROTECTION

SLOPED SILL AWAY TO
ENSURE WATER DRAINAGE

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

COMPRESSIBLE BACKER ROD
AND SEALANT

HIGH SLUMP MASONRY GROUT

ADAIR® LIMESTONE
MARBLE BASE COURSE

COMPRESSIBLE BACKER
ROD AND SEALANT

PREMOLDED EXPANSION JOINT FILLER

2% SLOPE MIN.

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM DOOR
ASSEMBLY

COMPRESSIBLE
BACKER ROD
AND SEALANT

FLOOR BY OTHER

BUILDING PAPER

AIR/VAPOR BARRIER



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

THRESHOLD OF DOOR
WITH ADAIR® BASE COURSE

DATE DRAWN:

08/30/04

DETAIL No:

SS 12S

SCALE:

3"=1'-0"

DRAWN BY:

LPS

U051