



GYPSUM WALLBOARD
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER
 MEMBRANE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON
 REQUIRED R-VALUE),
 MIN. 1" AIR SPACE,
 CALCIUM SILICATE MASONRY
 UNIT (CSMU).

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

MORTAR DROP
 CONTROL

UNOBSTRUCTED
 WEEP SYSTEM @ 24" O/C

WOOD BLOCKING

CORROSION PROTECTED
 STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
 ROD AND SEALANT

COMPRESSIBLE
 BACKER ROD AND
 SEALANT ALL
 AROUND THE FRAME

SPRAY APPLIED FOAM
 INSULATING AIR SEAL
 ALL AROUND FRAME

PREMANUFACTURED
 THERMALLY BROKEN
 ALUMINUM
 DOOR ASSEMBLY



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALTERNATIVE ALUMINUM
 DOOR HEAD**

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 SS 12S

U061