



GYPSUM WALLBOARD
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER MEMBRANE,
 RIGID OR SEMI-RIGID INSULATION
 (THICKNESS DEPENDANT ON
 REQUIRED R-VALUE),
 MIN. 1" AIR SPACE,
 CALCIUM SILICATE MASONRY
 UNIT (CSMU).

STEEL TRACK FASTENER
 (SCREW SIZE IS
 DETERMINED BY
 LOAD SUPPORTED)
 STEEL TRACK
 WELD PLATE
 CAST IN PLACE

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE
 MORTAR DROP
 CONTROL
 UNOBSTRUCTED
 WEEP SYSTEM @ 24" O/C
 COMPRESSIBLE
 BACKER ROD
 AND SEALANT
 3/8" MIN.
 CORROSION PROTECTED
 CONTINUOUS STEEL
 ANGLE AND STEEL BRACKET
 VENT @ 24" O/C
 INSULATION
 RETAINER
 ADJUSTABLE
 WALL TIE

LONG LEG OUTER
 TRACK ANCHORED TO
 SLAB, NEITHER SHEATHING
 OR DRYWALL ATTACHED
 TO ALLOW FOR
 DEFLECTION OF SLAB
 MINERAL FIBER
 FIRE STOP WHERE
 REQUIRED



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 ALTERNATIVE
 SHELF ANGLE/WALL

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 SS 12S

U081