



6" MIN.

3/8 MIN.
PARGING

INSULATION
RETAINER
ADJUSTABLE WALL TIE

MORTAR DROP
CONTROL

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

PREFINISHED
METAL DRIP EDGE
SET ON TWO
BEADS OF SEALANT

ADAIR® LIMESTONE
MASONRY UNIT,
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON REQUIRED
R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
EXTERIOR SHEATHING,
STEEL STUD WALL,
GYPSUM WALLBOARD.

COMPRESSIBLE BACKER
ROD AND SEALANT

STEEL TRACK FASTENER
(SCREW SIZE IS
DETERMINED BY
LOAD SUPPORTED)

STEEL TRACK

BUILDING PAPER
AIR/VAPOR BARRIER



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
FOUNDATION TO WALL
JUNCTION WITH SOIL

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
SS AD04S

U000