

ADAIR® LIMESTONE  
MASONRY UNIT,  
MIN. 1" AIR SPACE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON REQUIRED  
R-VALUE),  
AIR/VAPOR BARRIER  
MEMBRANE,  
EXTERIOR SHEATHING,  
STEEL STUD WALL,  
GYPSUM WALLBOARD.

SEALANT BEADS FOR  
MOISTURE PROTECTION

SLOPED SILL AWAY TO  
ENSURE WATER DRAINAGE

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

COMPRESSIBLE BACKER ROD  
AND SEALANT

HIGH SLUMP MASONRY GROUT

COMPRESSIBLE BACKER  
ROD AND SEALANT

PREMOLDED EXPANSION JOINT FILLER

2% SLOPE MIN.

PREMANUFACTURED  
THERMALLY BROKEN  
ALUMINUM DOOR  
ASSEMBLY

COMPRESSIBLE  
BACKER ROD  
AND SEALANT

FLOOR BY OTHER

BUILDING PAPER

AIR/VAPOR BARRIER



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

ALTERNATIVE  
THRESHOLD OF DOOR

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:  
SS AD04S

**U051**