



ADAIR® LIMESTONE
 MASONRY UNIT,
 MIN. 1" AIR SPACE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON REQUIRED
 R-VALUE),
 AIR/VAPOR BARRIER
 MEMBRANE,
 EXTERIOR SHEATHING,
 STEEL STUD WALL,
 GYPSUM WALLBOARD.

MORTAR DROP
 CONTROL

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

UNOBSTRUCTED
 WEEP SYSTEM @ 24" O/C

PREFINISHED
 METAL DRIP EDGE
 SET ON TWO
 BEADS OF SEALANT

STEEL TRACK FASTENER
 (SCREW SIZE IS
 DETERMINED BY
 LOAD SUPPORTED)

STEEL TRACK

6" MIN.

3/8 MIN.

COMPRESSIBLE
 BACKER ROD
 AND SEALANT

PREMOLDED
 EXPANSION
 JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER

HIGH SLUMP
 MASONRY GROUT



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 ALTERNATIVE FOUNDATION WALL/
 BURIED MASONRY UNIT

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 SS AD08S

U007