



ADAIR® LIMESTONE MASONRY UNIT, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, EXTERIOR SHEATHING, STEEL STUD WALL, GYPSUM WALLBOARD.

ADJUSTABLE WALL TIE  
INSULATION RETAINER

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

MORTAR DROP  
CONTROL

CORROSION PROTECTED  
CONTINUOUS STEEL  
ANGLE AND STEEL BRACKET

UNOBSTRUCTED  
WEEP SYSTEM @ 24" O/C

PREFINISHED  
METAL DRIP EDGE  
SET ON TWO BEADS  
OF SEALANT

3/8" MIN. PARGING

6" MIN.

COMPRESSIBLE BACKER  
ROD AND SEALANT

PREMOLDED EXPANSION  
JOINT FILLER

2% SLOPE MIN.

STEEL TRACK FASTENER  
(SCREW SIZE IS  
DETERMINED BY  
LOAD SUPPORTED)

STEEL TRACK

WELD PLATE  
CAST IN PLACE

AIR/VAPOR  
BARRIER

BUILDING PAPER

STEEL STUD  
FURRING WITH  
INSULATION



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
ALTERNATIVE FOUNDATION TO WALL  
(SHELF ANGLE) WITH PAVING

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:  
SS AD12S

**U009**