

ADAIR® LIMESTONE
 MASONRY UNIT,
 MIN. 1" AIR SPACE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON
 REQUIRED R-VALUE),
 AIR/VAPOR BARRIER
 MEMBRANE,
 EXTERIOR SHEATHING,
 STEED STUD WALL,
 GYPSUM WALLBOARD.

PREMANUFACTURED
 THERMALLY BROKEN
 ALUMINUM DOOR
 ASSEMBLY

COMPRESSIBLE BACKER
 ROD AND SEALANT

SEALANT BEADS FOR
 MOISTURE PROTECTION

SLOPED SILL AWAY TO
 ENSURE WATER DRAINAGE

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

FLOOR BY OTHER

PARGING

COMPRESSIBLE BACKER
 ROD AND SEALANT

PREMOLDED EXPANSION
 JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER

AIR/VAPOR BARRIER



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

THRESHOLD OF DOOR

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 SS AD12S

U050