

ADAIR® LIMESTONE
MASONRY UNIT,
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
AIR/VAPOR BARRIER
MEMBRANE,
EXTERIOR SHEATHING,
STEED STUD WALL,
GYPSUM WALLBOARD.

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM DOOR
ASSEMBLY

COMPRESSIBLE
BACKER ROD
AND SEALANT

FLOOR BY OTHER

SEALANT BEADS FOR
MOISTURE PROTECTION

SLOPED SILL AWAY TO
ENSURE WATER DRAINAGE

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

COMPRESSIBLE BACKER ROD
AND SEALANT

HIGH SLUMP MASONRY GROUT

COMPRESSIBLE BACKER
ROD AND SEALANT

PREMOLDED EXPANSION JOINT FILLER

2% SLOPE MIN.

BUILDING PAPER

AIR/VAPOR BARRIER



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

ALTERNATIVE
THRESHOLD OF DOOR

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
SS AD12S

U051