



ADAIR® LIMESTONE MASONRY UNIT, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, EXTERIOR SHEATHING, STEEL STUD WALL, GYPSUM WALLBOARD.

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

MORTAR DROP CONTROL

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

WOOD BLOCKING

CORROSION PROTECTED STEEL ANGLE LINTEL

COMPRESSIBLE BACKER ROD AND SEALANT

COMPRESSIBLE BACKER ROD AND SEALANT ALL AROUND THE FRAME

SPRAY APPLIED FOAM INSULATING AIR SEAL ALL AROUND FRAME

PREMANUFACTURED THERMALLY BROKEN ALUMINUM DOOR ASSEMBLY



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE: ALTERNATIVE ALUMINUM DOOR HEAD

DATE DRAWN: 08/30/04

SCALE: 3"=1'-0"

DRAWN BY: LPS

DETAIL No: SS AD12S

**U061**