



ADAIR® LIMESTONE
MASONRY UNIT,
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID INSULATION
(THICKNESS DEPENDANT ON
REQUIRED R-VALUE),
AIR/VAPOR BARRIER MEMBRANE,
EXTERIOR SHEATHING,
STEEL STUD WALL,
GYPSUM WALLBOARD.

STEEL TRACK FASTENER
(SCREW SIZE IS
DETERMINED BY
LOAD SUPPORTED)

STEEL TRACK

WELD PLATE
CAST IN PLACE

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

MORTAR DROP
CONTROL

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

COMPRESSIBLE
BACKER ROD
AND SEALANT

3/8" MIN.

CORROSION PROTECTED
CONTINUOUS STEEL
ANGLE AND STEEL BRACKET

VENT @ 24" O/C

INSULATION
RETAINER

ADJUSTABLE
WALL TIE

LONG LEG OUTER
TRACK ANCHORED TO
SLAB, NEITHER SHEATHING
OR DRYWALL ATTACHED
TO ALLOW FOR
DEFLECTION OF SLAB

MINERAL FIBER
FIRE STOP WHERE
REQUIRED



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
ALTERNATIVE
SHELF ANGLE/WALL

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
SS AD12S

U081