



MORTAR DROP CONTROL

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

ADAIR® LIMESTONE MARBLE BASE COURSE

HIGH SLUMP MASONRY GROUT

BALCONY SUPPORTED BY POSTS AT EXTERIOR EDGES

ADAIR® LIMESTONE MASONRY UNIT, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, EXTERIOR SHEATHING, STEEL STUD WALL, GYPSUM WALLBOARD.

STEEL TRACK FASTENER (SCREW SIZE IS DETERMINED BY LOAD SUPPORTED)

STEEL TRACK

2% SLOPE MIN.

WELD PLATE CAST IN PLACE

LONG LEG OUTER TRACK ANCHORED TO SLAB, NEITHER SHEATHING OR DRYWALL ATTACHED TO ALLOW FOR DEFLECTION OF SLAB

COMPRESSIBLE BACKER ROD AND SEALANT

VENT @ 24" O/C

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE: BALCONY/WALL WITH ADAIR® BASE COURSE

DATE DRAWN: 08/30/04

SCALE: 3"=1'-0"

DRAWN BY: LPS

DETAIL No: SS AD12S

U091