

NOTE: REFER TO
DOOR HEAD: SSAS3IU060

ATTACH SHEATHING WITH
APPROVED SCREWS
(TYPICAL @ EVERY STUD)

CALCIUM SILICATE STACK UNIT,
HI-BOND MASONRY VENEER MORTAR
- POLYMER FORTIFIED,
LATICRETE AIR & WATER BARRIER,
CEMENT BOARD,
EXTERIOR SHEATHING,
STEEL STUD WALL,
BATT INSULATION (THICKNESS
DEPENDENT ON REQUIRED R-VALUE),
VAPOR BARRIER (LOCATION
DEPENDENT ON CLIMATE ZONE),
GYPSUM WALLBOARD

ATTACH CEMENT BOARD
WITH APPROVED SCREWS
(TYPICAL @ EVERY STUD)

COMPRESSIBLE BACKER ROD AND
SEALANT ALL AROUND FRAME

SLOPED THRESHOLD SILL

WOOD BLOCKING

SPRAY APPLIED FOAM INSULATING
AIR SEAL ALL AROUND FRAME

PREMANUFACTURED THERMALLY
BROKEN ALUMINUM DOOR ASSEMBLY



ARRISCRAFT-CADD

DETAIL No:

SSAS3I

TITLE:
ALUMINUM DOOR JAMB
(PLAN VIEW)

U070

DATE DRAWN:
13 Jan 2021

SCALE:
3"=1'-0"

DRAWN BY:
TRI