



ADJUSTABLE WALL TIE
 INSULATION RETAINER
 FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE
 MORTAR DROP
 CONTROL
 UNOBSTRUCTED
 WEEP SYSTEM @ 24" O/C
 CORROSION PROTECTED
 STEEL ANGLE LINTEL
 COMPRESSIBLE BACKER
 ROD AND SEALANT
 PREMANUFACTURED
 THERMALLY BROKEN
 ALUMINUM
 WINDOW ASSEMBLY

GYPSUM WALLBOARD
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER
 MEMBRANE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON
 REQUIRED R-VALUE),
 MIN. 1" AIR SPACE,
 CALCIUM SILICATE
 BUILDING STONE.

WOOD BLOCKING
 COMPRESSIBLE
 BACKER ROD AND
 SEALANT ALL
 AROUND THE FRAME
 SPRAY APPLIED FOAM
 INSULATING AIR SEAL
 ALL AROUND FRAME



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALTERNATIVE ALUMINUM
 WINDOW HEAD**

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 SS CD3I

U031