



MORTAR DROP CONTROL
 FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE
 UNOBSTRUCTED WEEP SYSTEM @ 24" O/C
 PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

CALCIUM SILICATE BUILDING STONE, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, EXTERIOR SHEATHING, STEEL STUD WALL, GYPSUM WALLBOARD.

STEEL TRACK FASTENER (SCREW SIZE IS DETERMINED BY LOAD SUPPORTED)
 STEEL TRACK

CAST IN PLACE CONCRETE CURB
 BALCONY SUPPORTED BY POSTS AT EXTERIOR EDGES

2% SLOPE MIN.

WELD PLATE CAST IN PLACE

LONG LEG OUTER TRACK ANCHORED TO SLAB, NEITHER SHEATHING OR DRYWALL ATTACHED TO ALLOW FOR DEFLECTION OF SLAB

COMPRESSIBLE BACKER ROD AND SEALANT
 VENT @ 24" O/C
 CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

BALCONY/WALL

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:

SS CD3I

U090