



GYPSUM WALLBOARD,
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER
 MEMBRANE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON REQUIRED
 R-VALUE),
 MIN. 1" AIR SPACE,
 CALCIUM SILICATE BUILDING STONE.

HORIZONTAL REINFORCING
 IN BED JOINTS TO REINFORCE
 CONTINUOUS VERTICAL CORNER JOINTS

RAKE BACK MORTAR BETWEEN
 UNITS APPROX. 1" DEEP. COVER
 WITH BACKER ROD AND SEALANT
 TO PROTECT MORTAR

VERTICAL JOINT BETWEEN
 ROCKED UNITS IN
 COURSE ABOVE AND BELOW

INSULATION RETAINER

ADJUSTABLE WALL TIE



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

OUTSIDE QUIRK
 MITERED CORNER

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:

SS CD3I

U150