



ADJUSTABLE WALL TIE  
INSULATION RETAINER

CALCIUM SILICATE BUILDING STONE, MIN. 25 MM AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOUR BARRIER MEMBRANE, EXTERIOR SHEATHING, STEEL STUD WALL, GYPSUM WALLBOARD.

MORTAR DROP CONTROL

FLASHING MEMBRANE SURFACE ADHERED TO SUBSTRATE

UNOBSTRUCTED WEEP SYSTEM @ 600 MM O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

PARGING

STEEL TRACK FASTENER (SCREW SIZE IS DETERMINED BY LOAD SUPPORTED)

STEEL TRACK

150 MIN.  
10 MIN.  
2% SLOPE MIN.

COMPRESSIBLE BACKER ROD AND SEALANT  
PREMOULDED EXPANSION JOINT FILLER

BUILDING PAPER  
STEEL STUD FURRING WITH INSULATION  
GYPSUM BOARD  
AIR/VAPOUR BARRIER



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
ALTERNATIVE FOUNDATION TO WALL  
JUNCTION

DATE DRAWN:  
08/30/04

SCALE:  
1:5

DRAWN BY:  
LPS

DETAIL No:  
SS CD3M

**D003**