



ADJUSTABLE WALL TIE
INSULATION RETAINER

MORTAR DROP CONTROL

FLASHING MEMBRANE SURFACE ADHERED TO SUBSTRATE

UNOBSTRUCTED WEEP SYSTEM @ 600 MM O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

ADAIR® LIMESTONE MARBLE BASE COURSE

150 MIN.
COMPRESSIBLE BACKER ROD AND SEALANT

PREMOULDED EXPANSION JOINT FILLER

2% SLOPE MIN.

GYPSUM WALLBOARD,
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOUR BARRIER
MEMBRANE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON REQUIRED
R-VALUE),
MIN. 25 MM AIR SPACE,
CALCIUM SILICATE
BUILDING STONE.

STEEL TRACK FASTENER
(SCREW SIZE IS
DETERMINED BY
LOAD SUPPORTED)

STEEL TRACK

BUILDING PAPER

AIR/VAPOUR BARRIER



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE: FOUNDATION WALL/
BURIED MASONRY UNIT
(ADAIR® LIMESTONE BASE COURSE)

DATE DRAWN:
08/30/04

SCALE:
1:5

DRAWN BY:
LPS

DETAIL No:
SS CD3M

D006