



ADJUSTABLE WALL TIE
INSULATION RETAINER

GYPSUM WALLBOARD,
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOUR BARRIER
MEMBRANE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON REQUIRED
R-VALUE),
MIN. 25 MM AIR SPACE,
CALCIUM SILICATE
BUILDING STONE.

MORTAR DROP CONTROL
FLASHING MEMBRANE SURFACE
ADHERED TO SUBSTRATE

STEEL TRACK FASTENER
(SCREW SIZE IS
DETERMINED BY
LOAD SUPPORTED)

UNOBSTRUCTED
WEEP SYSTEM @ 600 MM O/C
PREFINISHED METAL DRIP EDGE
SET ON TWO BEADS OF SEALANT

STEEL TRACK

10 MIN.
PROTECTION BOARD

AIR/VAPOUR BARRIER
BUILDING PAPER



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE: FOUNDATION WALL/
BURIED MASONRY UNIT
(PROTECTION BOARD)

DATE DRAWN:
08/30/04

SCALE:
1:5

DRAWN BY:
LPS

DETAIL No:
SS CD3M

D009