



MORTAR DROP CONTROL

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

UNOBSTRUCTED WEEP SYSTEM @ 600 MM O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

ADAIR® LIMESTONE BASE COURSE

HIGH SLUMP MASONRY GROUT

BALCONY SUPPORTED BY POSTS AT EXTERIOR EDGES

CALCIUM SILICATE BUILDING STONE, MIN. 25 MM AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOUR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU), METAL FURRING (OPTIONAL), GYPSUM WALLBOARD.

STEEL TRACK FASTENER (SCREW SIZE IS DETERMINED BY LOAD SUPPORTED)

STEEL TRACK

COMPRESSIBLE BACKER ROD AND SEALANT

VENT @ 600 MM O/C

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

WELD PLATE CAST IN PLACE

LONG LEG OUTER TRACK ANCHORED TO SLAB, NEITHER SHEATHING OR DRYWALL ATTACHED TO ALLOW FOR DEFLECTION OF SLAB



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
BALCONY/WALL
WITH ADAIR® BASE COURSE

DATE DRAWN:
08/30/04

SCALE:
1:5

DRAWN BY:
LPS

DETAIL No:
SS CD3M

D091