



PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM DOOR
ASSEMBLY

SEALANT BEADS FOR
MOISTURE PROTECTION

SLOPE SILL AWAY TO
ENSURE WATER DRAINAGE

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

CAST IN PLACE
CONCRETE CURB

BALCONY SUPPORTED BY
POSTS AT EXTERIOR EDGES

CAST IN PLACE
CONCRETE
CURB

VERTICAL REINFORCING
IF REQUIRED

COMPRESSIBLE BACKER
ROD AND SEALANT

VENT @ 600 MM O/C

CORROSION PROTECTED
CONTINUOUS STEEL
ANGLE AND STEEL BRACKET

WELD PLATE
CAST IN PLACE

LONG LEG OUTER
TRACK ANCHORED TO
SLAB, NEITHER SHEATHING
OR DRYWALL ATTACHED TO
ALLOW FOR DEFLECTION
OF SLAB



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:

BALCONY/WALL
AT PATIO DOOR

DATE DRAWN:
08/30/04

SCALE:
1:5

DRAWN BY:
LPS

DETAIL No:
SS CD3M

D092