



ADJUSTABLE WALL TIE
INSULATION RETAINER

GYPSUM WALLBOARD
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER
MEMBRANE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
CALCIUM SILICATE
BUILDING STONE.

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

MORTAR DROP
CONTROL

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

PREFINISHED
METAL DRIP EDGE
SET ON TWO
BEADS OF SEALANT

WOOD BLOCKING

CORROSION PROTECTED
STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
ROD AND SEALANT

COMPRESSIBLE
BACKER ROD AND
SEALANT ALL
AROUND THE FRAME

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM
DOOR ASSEMBLY

SPRAY APPLIED FOAM
INSULATING AIR SEAL
ALL AROUND FRAME



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALUMINUM DOOR
HEAD**

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
SS CD4I
U060