



CALCIUM SILICATE BUILDING STONE, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, EXTERIOR SHEATHING, STEEL STUD WALL, GYPSUM WALLBOARD.

COMPRESSIBLE BACKER ROD AND SEALANT
 STEEL TRACK FASTENER (SCREW SIZE IS DETERMINED BY LOAD SUPPORTED)
 STEEL TRACK

BUILDING PAPER
 AIR/VAPOR BARRIER

6" MIN.
 3/8 MIN.
 PARGING

INSULATION RETAINER
 ADJUSTABLE WALL TIE
 MORTAR DROP CONTROL
 FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE
 UNOBSTRUCTED WEEP SYSTEM @ 24" O/C
 PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 FOUNDATION TO WALL
 JUNCTION WITH SOIL

DATE DRAWN:
 09/13/11

SCALE:
 3"=1'-0"

DRAWN BY:
 DDN

DETAIL No:
 SS CU3

U000