



WOOD BLOCKING  
 BACKER ROD AND SEALANT  
 BULLNOSE SILL CALCIUM SILICATE MASONRY UNIT (CSMU)  
 MASONRY TIE OR MECHANICAL ANCHOR IN HEAD JOINT  
 RAKE BACK MORTAR BETWEEN UNITS APPROX. 1" DEEP. COVER WITH BACKER ROD AND SEALANT TO PROTECT MORTAR

PREMANUFACTURED THERMALLY BROKEN ALUMINUM WINDOW ASSEMBLY  
 SPRAY APPLIED FOAM INSULATING AIR SEAL ALL AROUND FRAME  
 BACKER ROD AND SEALANT ALL AROUND THE FRAME  
 WOOD BLOCKING

1" MIN.  
 UNDERSILL FLASHING MEMBRANE C/W END DAMS, INSTALL TUBE VENTS AT CENTER OF BULLNOSE UNITS  
 VENT @ 24" O/C

GYPSUM WALLBOARD  
 STEEL STUD WALL,  
 EXTERIOR SHEATHING,  
 AIR/VAPOR BARRIER MEMBRANE,  
 RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE),  
 MIN. 1" AIR SPACE,  
 CALCIUM SILICATE BUILDING STONE.



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

**BULLNOSE WINDOW SILL**

DATE DRAWN:  
 09/13/11

SCALE:  
 3"=1'-0"

DRAWN BY:  
 DDN

DETAIL No:

SS CU3

**U021**