



CALCIUM SILICATE  
BUILDING STONE,  
MIN. 1" AIR SPACE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON REQUIRED  
R-VALUE),  
AIR/VAPOR BARRIER  
MEMBRANE (SHEET),  
EXTERIOR SHEATHING,  
STEEL STUD WALL,  
GYPSUM WALLBOARD.

SEALANT BEADS FOR  
MOISTURE PROTECTION

SLOPE SILL AWAY TO  
ENSURE WATER DRAINAGE

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

COMPRESSIBLE BACKER  
ROD AND SEALANT

ADAIR® LIMESTONE  
MARBLE BASE COURSE

HIGH SLUMP MASONRY GROUT

COMPRESSIBLE BACKER  
ROD AND SEALANT

PREMOLDED EXPANSION  
JOINT FILLER

2% SLOPE MIN.

PREMANUFACTURED  
THERMALLY BROKEN  
ALUMINUM DOOR  
ASSEMBLY

COMPRESSIBLE  
BACKER ROD  
AND SEALANT

FLOOR BY OTHER

BUILDING PAPER

AIR/VAPOR BARRIER



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
THRESHOLD OF DOOR  
WITH ADAIR® BASE COURSE

DATE DRAWN:  
09/13/11

SCALE:  
3"=1'-0"

DRAWN BY:  
DDN

DETAIL No:  
SS CU3

**U051**