



GYPSUM WALLBOARD
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER MEMBRANE,
 RIGID OR SEMI-RIGID INSULATION
 (THICKNESS DEPENDANT ON
 REQUIRED R-VALUE),
 MIN. 1" AIR SPACE,
 CALCIUM SILICATE
 BUILDING STONE.

STEEL TRACK FASTENER
 (SCREW SIZE IS
 DETERMINED BY
 LOAD SUPPORTED)

STEEL TRACK

WELD PLATE
 CAST IN PLACE

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

MORTAR DROP
 CONTROL

UNOBSTRUCTED
 WEEP SYSTEM @ 24" O/C

COMPRESSIBLE
 BACKER ROD
 AND SEALANT

3/8" MIN.

CORROSION PROTECTED
 CONTINUOUS STEEL
 ANGLE AND STEEL BRACKET

VENT @ 24" O/C

INSULATION
 RETAINER

ADJUSTABLE
 WALL TIE

LONG LEG OUTER
 TRACK ANCHORED TO
 SLAB, NEITHER SHEATHING
 OR DRYWALL ATTACHED
 TO ALLOW FOR
 DEFLECTION OF SLAB

MINERAL FIBER
 FIRE STOP WHERE
 REQUIRED



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 ALTERNATIVE
 SHELF ANGLE/WALL

DATE DRAWN:
 09/13/11

SCALE:
 3"=1'-0"

DRAWN BY:
 DDN

DETAIL No:
 SS CU3

U081