



WOOD BLOCKING

BACKER ROD AND SEALANT

1" MIN.

VENT @ 24" O/C

CALCIUM SILICATE BUILDING STONE
MIN. 1" AIR SPACE,
RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE),
AIR/VAPOR BARRIER MEMBRANE,
CONCRETE MASONRY UNIT (CMU).

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

MORTAR DROP CONTROL

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

PREFINISHED METAL DRIP EDGE SET ON TWO BEADS OF SEALANT

3/8" MIN.

COMPRESSIBLE BACKER ROD AND SEALANT

WELD PLATE CAST IN PLACE

METAL CAP FLASHING

BOLT

FLEXIBLE FLASHING MEMBRANE BELOW METAL CAP

COVERBOARD

VERTICAL REINFORCING IF REQUIRED

ROOF BY OTHER

LONG LEG OUTER TRACK ANCHORED TO SLAB, NEITHER SHEATHING OR DRYWALL ATTACHED TO ALLOW FOR DEFLECTION OF SLAB



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE: HIGH PARAPET TO WALL WITH METAL CAP FLASHING

DATE DRAWN: 09/13/11

SCALE: 3"=1'-0"

DRAWN BY: DDN

DETAIL No: SS CU3

U122