



ADJUSTABLE WALL TIE  
INSULATION RETAINER

GYPSUM WALLBOARD  
STEEL STUD WALL,  
EXTERIOR SHEATHING,  
AIR/VAPOR BARRIER  
MEMBRANE,  
RIGID OR SEMI-RIGID  
INSULATION (THICKNESS  
DEPENDANT ON  
REQUIRED R-VALUE),  
MIN. 1" AIR SPACE,  
CALCIUM SILICATE  
BUILDING STONE.

FLASHING MEMBRANE  
SURFACE ADHERE  
TO SUBSTRATE

MORTAR DROP  
CONTROL

UNOBSTRUCTED  
WEEP SYSTEM @ 24" O/C

PREFINISHED  
METAL DRIP EDGE  
SET ON TWO  
BEADS OF SEALANT

WOOD BLOCKING

CORROSION PROTECTED  
STEEL ANGLE LINTEL

COMPRESSIBLE BACKER  
ROD AND SEALANT

COMPRESSIBLE  
BACKER ROD AND  
SEALANT ALL  
AROUND THE FRAME

PREMANUFACTURED  
THERMALLY BROKEN  
ALUMINUM  
DOOR ASSEMBLY

SPRAY APPLIED FOAM  
INSULATING AIR SEAL  
ALL AROUND FRAME



**ARRISCRAFT**  
INTERNATIONAL  
BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
**ALUMINUM DOOR  
HEAD**

DATE DRAWN:  
08/30/04

SCALE:  
3"=1'-0"

DRAWN BY:  
LPS

DETAIL No:  
SS LR3I

**U060**