



INSULATION
RETAINER
ADJUSTABLE
WALL TIE

GYPSUM WALLBOARD
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER MEMBRANE,
RIGID OR SEMI-RIGID INSULATION
(THICKNESS DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
CALCIUM SILICATE
BUILDING STONE.

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

STEEL TRACK FASTENER
(SCREW SIZE IS
DETERMINED BY
LOAD SUPPORTED)

MORTAR DROP
CONTROL

STEEL TRACK

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

WELD PLATE
CAST IN PLACE

COMPRESSIBLE
BACKER ROD
AND SEALANT

3/8" MIN.

CORROSION PROTECTED
CONTINUOUS STEEL
ANGLE AND STEEL BRACKET

LONG LEG OUTER
TRACK ANCHORED TO
SLAB, NEITHER SHEATHING
OR DRYWALL ATTACHED
TO ALLOW FOR
DEFLECTION OF SLAB

VENT @ 24" O/C

MINERAL FIBER
FIRE STOP WHERE
REQUIRED



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALTERNATIVE
SHELF ANGLE/WALL**

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
SS LR3I

U081