



ADJUSTABLE WALL TIE
INSULATION RETAINER

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

MORTAR DROP
CONTROL

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

CORROSION PROTECTED
STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
ROD AND SEALANT

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM
WINDOW ASSEMBLY

GYPSUM WALLBOARD
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER
MEMBRANE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
CALCIUM SILICATE
BUILDING STONE.

WOOD BLOCKING

COMPRESSIBLE
BACKER ROD AND
SEALANT ALL
AROUND THE FRAME

SPRAY APPLIED FOAM
INSULATING AIR SEAL
ALL AROUND FRAME

Arriscraft
Building Stone · Brick · Limestone

ARRISCRAFT • CADD

DETAIL No:
SS OC3I

TITLE:
ALTERNATIVE ALUMINUM
WINDOW HEAD

U031

DATE DRAWN:
09/10/12

SCALE:
3"=1'-0"

DRAWN BY:
TRI