



ADJUSTABLE WALL TIE
INSULATION RETAINER

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

MORTAR DROP
CONTROL

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

PREFINISHED
METAL DRIP EDGE
SET ON TWO
BEADS OF SEALANT

CORROSION PROTECTED
STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
ROD AND SEALANT

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM
DOOR ASSEMBLY

GYPSUM WALLBOARD
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER
MEMBRANE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
CALCIUM SILICATE
BUILDING STONE.

WOOD BLOCKING

COMPRESSIBLE
BACKER ROD AND
SEALANT ALL
AROUND THE FRAME

SPRAY APPLIED FOAM
INSULATING AIR SEAL
ALL AROUND FRAME

Arriscraft
Building Stone · Brick · Limestone

ARRISCRAFT • CADD

DETAIL No:
SS OC31

TITLE:
ALUMINUM DOOR
HEAD

U060

DATE DRAWN:
09/10/12

SCALE:
3"=1'-0"

DRAWN BY:
TRI