



MECHANICAL ANCHOR

10  
1

RAKE BACK MORTAR BETWEEN UNITS APPROX. 1" DEEP COVER WITH BACKER ROD AND SEALANT TO PROTECT MORTAR

STONE OR PRECAST CAP

1" MIN.  
1-1/2" MIN.

1" MIN.  
1-1/2" MIN.

VENT @ 24" O/C

FLEXIBLE FLASHING MEMBRANE BELOW STONE OR PRECAST CAP

CALCIUM SILICATE BUILDING STONE, MIN. 1" AIR SPACE, RIGID OR SEMI-RIGID INSULATION (THICKNESS DEPENDANT ON REQUIRED R-VALUE), AIR/VAPOR BARRIER MEMBRANE, CONCRETE MASONRY UNIT (CMU).

VERTICAL REINFORCING WHEN REQUIRED

COVERBOARD

ROOF BY OTHER

FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE

MORTAR DROP CONTROL

WELD PLATE CAST IN PLACE

CORROSION PROTECTED CONTINUOUS STEEL ANGLE AND STEEL BRACKET

UNOBSTRUCTED WEEP SYSTEM @ 24" O/C

COMPRESSIBLE BACKER ROD AND SEALANT

LONG LEG OUTER TRACK ANCHORED TO SLAB, NEITHER SHEATHING OR DRYWALL ATTACHED TO ALLOW FOR DEFLECTION OF SLAB

**Arriscraft**  
Building Stone · Brick · Limestone

**ARRISCRAFT • CADD**

DETAIL No:

SS OC31

TITLE:

ALTERNATIVE PARAPET TO WALL WITH STONE OR PRECAST CAP

**U125**

DATE DRAWN:  
09/10/12

SCALE:  
3"=1'-0"

DRAWN BY:  
TRI