



GYPSUM WALLBOARD  
 STEEL STUD WALL,  
 EXTERIOR SHEATHING,  
 AIR/VAPOR BARRIER  
 MEMBRANE,  
 RIGID OR SEMI-RIGID  
 INSULATION (THICKNESS  
 DEPENDANT ON  
 REQUIRED R-VALUE),  
 MIN. 1" AIR SPACE,  
 CALCIUM SILICATE  
 BUILDING STONE.

WOOD BLOCKING

COMPRESSIBLE  
 BACKER ROD AND  
 SEALANT ALL  
 AROUND THE FRAME

SPRAY APPLIED FOAM  
 INSULATING AIR SEAL  
 ALL AROUND FRAME

ADJUSTABLE WALL TIE  
 INSULATION RETAINER

FLASHING MEMBRANE  
 SURFACE ADHERE  
 TO SUBSTRATE

MORTAR DROP  
 CONTROL

UNOBSTRUCTED  
 WEEP SYSTEM @ 24" O/C

CORROSION PROTECTED  
 STEEL ANGLE LINTEL

COMPRESSIBLE BACKER  
 ROD AND SEALANT

PREMANUFACTURED  
 THERMALLY BROKEN  
 ALUMINUM  
 WINDOW ASSEMBLY



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:  
**ALTERNATIVE ALUMINUM  
 WINDOW HEAD**

DATE DRAWN:  
 08/30/04

SCALE:  
 3"=1'-0"

DRAWN BY:  
 LPS

DETAIL No:  
 SS SH2I

**U031**