



GYPSUM WALLBOARD
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER MEMBRANE,
 RIGID OR SEMI-RIGID INSULATION
 (THICKNESS DEPENDANT ON
 REQUIRED R-VALUE),
 MIN. 1" AIR SPACE,
 CALCIUM SILICATE
 BUILDING STONE.

STEEL TRACK FASTENER
 (SCREW SIZE IS
 DETERMINED BY
 LOAD SUPPORTED)

STEEL TRACK
 WELD PLATE
 CAST IN PLACE

LONG LEG OUTER
 TRACK ANCHORED TO
 SLAB, NEITHER SHEATHING
 OR DRYWALL ATTACHED
 TO ALLOW FOR
 DEFLECTION OF SLAB

MINERAL FIBER
 FIRE STOP WHERE
 REQUIRED



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
 SHELF ANGLE/WALL

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 SS SH2I

U080