



GYPSUM WALLBOARD,  
 STEEL STUD WALL,  
 EXTERIOR SHEATHING,  
 AIR/VAPOR BARRIER  
 MEMBRANE,  
 RIGID OR SEMI-RIGID  
 INSULATION (THICKNESS  
 DEPENDANT ON REQUIRED  
 R-VALUE),  
 MIN. 1" AIR SPACE,  
 CALCIUM SILICATE BUILDING STONE.

HORIZONTAL REINFORCING  
 IN BED JOINTS TO REINFORCE  
 CONTINUOUS VERTICAL CORNER JOINTS

RAKE BACK MORTAR BETWEEN  
 UNITS APPROX. 1" DEEP. COVER  
 WITH BACKER ROD AND SEALANT  
 TO PROTECT MORTAR

VERTICAL JOINT BETWEEN  
 ROCKED UNITS IN  
 COURSE ABOVE AND BELOW

INSULATION RETAINER

ADJUSTABLE WALL TIE



**ARRISCRAFT**  
 INTERNATIONAL  
 BUILDING STONE • BRICK • LIMESTONE

**ARRISCRAFT • CADD**

TITLE:

OUTSIDE QUIRK  
 MITERED CORNER

DATE DRAWN:  
 08/30/04

SCALE:  
 3"=1'-0"

DRAWN BY:  
 LPS

DETAIL No:

SS SH2I

**U150**