



GYPSUM WALLBOARD
 STEEL STUD WALL,
 EXTERIOR SHEATHING,
 AIR/VAPOR BARRIER
 MEMBRANE,
 RIGID OR SEMI-RIGID
 INSULATION (THICKNESS
 DEPENDANT ON
 REQUIRED R-VALUE),
 MIN. 1" AIR SPACE,
 CALCIUM SILICATE
 BUILDING STONE.

WOOD BLOCKING

COMPRESSIBLE
 BACKER ROD AND
 SEALANT ALL
 AROUND THE FRAME

SPRAY APPLIED FOAM
 INSULATING AIR SEAL
 ALL AROUND FRAME

ADJUSTABLE WALL TIE
 INSULATION RETAINER

FLASHING MEMBRANE
 SURFACE ADHERE
 TO SUBSTRATE

MORTAR DROP
 CONTROL

UNOBSTRUCTED
 WEEP SYSTEM @ 24" O/C

CORROSION PROTECTED
 STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
 ROD AND SEALANT

PREMANUFACTURED
 THERMALLY BROKEN
 ALUMINUM
 WINDOW ASSEMBLY



ARRISCRAFT
 INTERNATIONAL
 BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALTERNATIVE ALUMINUM
 WINDOW HEAD**

DATE DRAWN:
 08/30/04

SCALE:
 3"=1'-0"

DRAWN BY:
 LPS

DETAIL No:
 SS SH3I

U031