



ADJUSTABLE WALL TIE
INSULATION RETAINER

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

MORTAR DROP
CONTROL

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

CORROSION PROTECTED
STEEL ANGLE LINTEL

COMPRESSIBLE BACKER
ROD AND SEALANT

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM
DOOR ASSEMBLY

GYPSUM WALLBOARD
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER
MEMBRANE,
RIGID OR SEMI-RIGID
INSULATION (THICKNESS
DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
CALCIUM SILICATE
BUILDING STONE.

WOOD BLOCKING

COMPRESSIBLE
BACKER ROD AND
SEALANT ALL
AROUND THE FRAME

SPRAY APPLIED FOAM
INSULATING AIR SEAL
ALL AROUND FRAME



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
**ALTERNATIVE ALUMINUM
DOOR HEAD**

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
SS SH3I

U061