



INSULATION
RETAINER
ADJUSTABLE
WALL TIE

FLASHING MEMBRANE
SURFACE ADHERE
TO SUBSTRATE

MORTAR DROP
CONTROL

UNOBSTRUCTED
WEEP SYSTEM @ 24" O/C

PREFINISHED
METAL DRIP EDGE
SET ON TWO BEADS
OF SEALANT

COMPRESSIBLE
BACKER ROD
AND SEALANT

CORROSION PROTECTED
CONTINUOUS STEEL
ANGLE AND STEEL BRACKET

VENT @ 24" O/C

GYPSUM WALLBOARD
STEEL STUD WALL,
EXTERIOR SHEATHING,
AIR/VAPOR BARRIER MEMBRANE,
RIGID OR SEMI-RIGID INSULATION
(THICKNESS DEPENDANT ON
REQUIRED R-VALUE),
MIN. 1" AIR SPACE,
CALCIUM SILICATE
BUILDING STONE.

STEEL TRACK FASTENER
(SCREW SIZE IS
DETERMINED BY
LOAD SUPPORTED)

STEEL TRACK

WELD PLATE
CAST IN PLACE

LONG LEG OUTER
TRACK ANCHORED TO
SLAB, NEITHER SHEATHING
OR DRYWALL ATTACHED
TO ALLOW FOR
DEFLECTION OF SLAB

MINERAL FIBER
FIRE STOP WHERE
REQUIRED



ARRISCRAFT
INTERNATIONAL
BUILDING STONE • BRICK • LIMESTONE

ARRISCRAFT • CADD

TITLE:
SHELF ANGLE/WALL

DATE DRAWN:
08/30/04

SCALE:
3"=1'-0"

DRAWN BY:
LPS

DETAIL No:
SS SH3I

U080